



Product Data Sheet

FL1701 Recirculating Cooler/Chiller

[Print Data Sheet](#)

Product Image



Order Information

Model: FL1701
Order no.: 9661017

Available mains power:
 230V / 50Hz
 115V / 60Hz
 230V / 60Hz

Downloads

+ [EasyTemp Software](#)

Similar Models

These models could also be interesting for you:

[FL1203](#)
[FL1703](#)

Sales & Support:

+49 7823 51-190

Monday to Friday
 7:30 am - 17:00 pm

JULABO Labortechnik GmbH
 Eisenbahnstrasse 45
 77960 Seelbach/Germany
 Phone +49 7823 51-0
 Fax +49 7823 2491
info@julabo.de
www.julabo.de

Technical changes reserved.
 Pictures may differ from original.

Distributed by:



Carl Stuart Limited

ADVANCED APPLIED TECHNOLOGIES

Contact Us:

Irl Ph: 01 4523432
 UK Ph: 08452 30 40 30
 Web: www.carlstuart.com
 Email: info@carlstuart.com

Description

Recirculating Cooler/Chiller for environmentally friendly cooling

The FL series offers a new generation of chillers for routine cooling applications within the laboratory and industry. The working temperature range covers -20°C to $+40^{\circ}\text{C}$, the temperature stability of the PID control is $\pm 0.5^{\circ}\text{C}$. All units can easily be cleaned and are provided with a splash water proof keypad with LED temperature indication. On the front of the units there is an RS232 interface as well as an alarm shutdown. The filling port is easily accessible placed on the top under a lift-up cover. Another hinged tray serves as a file for the operating manual or other documents concerning the installation. The removable venting grid allows an easy cleaning of the condenser, the drain tap is easily accessible behind the grid. All models include an easily visible level indication. Another advantage is the venting slots are on the front and rear and therefore the units can be placed directly one beside the other (space saving).

Advantages

- o Ergonomic design and easy operation
- o Splash-proof keypad with integrated mains switch
- o Large, bright LED display
- o Reliable Microprocessor PID temperature control
- o Filling level indicator
- o Powerful immersion pumps, suitable for continuous operation
- o Permissible temperature in return line $+80^{\circ}\text{C}$
- o Easy filling from the top with hinged protective lid
- o Low liquid level protection with optical and audible alarm signal
- o Integrated stainless steel bath tanks
- o Removable venting grid for cleaning of the condenser
- o Front drain
- o No side vents
- o RS232 interface for PC-connection
- o IP class according to IEC 60529: 21
- o Pressure indicator
- o Adjustable bypass for pump pressure

Technical Specifications

Working temperature range	-20 ... 40 °C
Temperature control	PID
Temperature stability	$\pm 0.5^{\circ}\text{C}$
Display	LED
Display resolution	0.1 °C
Integrated programmer	not available
Heater capacity	0 W
Cooling capacity	20 10 0 -10 -20 °C 1700 1500 1100 850 400 W
Refrigerant	R404a
Pump capacity	Pressure: 1000 mbar Flow rate: 40 l/min
Digital interfaces	RS232
Filling volume	12 ... 17 Liters
Dimensions (W x L x H)	50 x 76 x 64 cm
Weight	71 kg
Ambient temperature	5...40 °C
Classification according to DIN 12876-1	-

Miscellaneous

Included: 2 each barbed fittings for tubing 8 and 12 mm inner dia. (pump connections M16x1 male)
 Suitable fluids: water, water-glycol mixture, JULABO Thermal bath fluids